

CONVERGENT CONNECTIVITY *TECHNOLOGY*

WB1027

18/6 Stranded bare copper conductors, shielded, wrapped **Description:**

with a water-blocking tape and overall jacketed

Applications: Intercom Systems, Security Systems, Sound and Audio, Background Music, and

Power-Limited Control Circuits. Outdoor Applications



Conductor: 18 AWG Bare Copper

7 Strand Stranding:

Insulation Material: Polyvinyl Chloride

Insulation Thickness: 0.008 in. (0.203 mm.) Nominal

Number of Conductors or Pairs: 6 Conductor

Shield: Aluminum/Polyester Tape (100% Coverage)

Drain: Stranded Tin Copper

Water blocking tape Tape:

Jacket Material: Polyethylene

Jacket Thickness: 0.025 in. (0.635 mm.) Nominal

Overall Cable Diameter: 0.261 in. (6.629 mm.) Nominal

Approx Cable Weight /1,000 ft.: 50 lbs.

ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage: 300 V, RMS

Insulation Colors: Black, Red, White, Green, Blue,

Brown

Min. Bend Radius (Installation): 4.000 in.

 -20° C to $+60^{\circ}$ C Temperature Rating:

> Issue Date: August '15 Revision: 0

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744 FAX: 845-651-3564

PO BOX 454 FLORIDA, NY 10921



CONVERGENT CONNECTIVITY TECHNOLOGY

WB1027



Note: While Convergent Connectivity Technology has made every reasonable effort to ensure the accuracy of the information in this document, Convergent Connectivity Technology does not guarantee that it is error-free, nor does Convergent Connectivity Technology make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Convergent Connectivity Technology reserves the right to make any adjustments to the information contained herein at any time without notice. Convergent Connectivity Technology expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.	
Signature:	
Company:	
Date:	

Your signature constitutes that you have read and agreed to

Issue Date: August '15 Revision: 0

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744 FAX: 845-651-3564