

CONVERGENT CONNECTIVITY TECHNOLOGY

725212

18/3 Stranded bare copper conductors, shielded with an overall jacket **Description:**

NEC Article 800, UL Subject 444, Type CMP, C(ETL)US, RoHS Compliant **Ratings/Approvals:**

Applications: Intercom Systems, Security Systems, Sound and Audio, Background Music, and

Power-Limited Control Circuits. Indoor Applications

CONSTRUCTION

Conductor: 18 AWG Bare Copper

7 Strand Stranding:

Insulation Material: Low Smoke PVC

Insulation Thickness: 0.007 in. (0.177 mm.) Nominal

Number of Conductors or Pairs: 3 Conductor

Aluminum/Polyester Tape(100% Coverage) Shield:

Drain: Stranded Tin Copper

Jacket Material: Low Smoke PVC

Jacket Thickness: 0.015 in. (0.381 mm.) Nominal

Overall Cable Diameter: 0.161 in. (4.089 mm.) Nominal

26 lbs. Approx Cable Weight /1,000 ft.:

ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage: **300 V RMS**

Insulation Colors: Black, Natural, Red

DC Resistance per Conductor @ 20°C: $6.6\Omega/1\text{m}$

Temperature Rating: -2° C to $+60^{\circ}$ C

Issue Date: December '15 Revision: 3

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744 FAX: 845-651-3564

PO BOX 454 FLORIDA, NY 10921



CONVERGENT CONNECTIVITY TECHNOLOGY

725215

Note: While Convergent Connectivity Technology has made every reasonable effort to ensure the accuracy of the information in this document, Convergent Connectivity Technology does not guarantee that it is error-free, nor does Convergent Connectivity Technology make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Convergent Connectivity Technology reserves the right to make any adjustments to the information contained herein at any time without notice. Convergent Connectivity Technology expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

this specification	onstitutes that you have read and agreed to sheet and upon confirmation of your order; non-cancelable and non-returnable.
Signature:	
Company:	
Date:	

Issue Date: December '15 Revision: 3

THE STRONGEST LINK IN YOUR SUPPLY CHAIN



PHONE: 866-905-6744 FAX: 845-651-3564

PO BOX 454 FLORIDA, NY 10921