



725820

18/20 Stranded bare copper conductors, unshielded with an overall jacket **Description:**

NEC Article 800, UL Subject 444, Type CMP, C(ETL)US, RoHS Compliant **Ratings/Approvals:**

Applications: Intercom Systems, Security Systems, Sound and Audio, Background Music, and Power-Limited Control Circuits. Indoor Applications

CONSTRUCTION

Conductor: 18 AWG Bare Copper

Stranding: 7 Strand

Insulation Material: Plenum Polymer

Insulation Thickness: 0.008 in. (0.203 mm.) Nominal

Number of Conductors or Pairs: 20 Conductor

Shield: N/A

Drain: N/A

Jacket Material: Plenum Polymer

Jacket Thickness: 0.020 in. (0.508 mm.) Nominal

Overall Cable Diameter: 0.360 in. (9.167 mm.) Nominal

Approx Cable Weight /1,000 ft.: 148 lbs.

ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage: 300 V, RMS

Insulation Colors: White number coded one thru

twenty

 $6.5\Omega/1\text{m}$ DC Resistance per Conductor @ 20°C:

5.5 in. Min. Bend Radius (Installation):

Issue Date: February '24

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

RoHS∜

PHONE: 866-905-6744 FAX: 845-651-3564

PO BOX 454 FLORIDA, NY 10921



CONVERGENT CONNECTIVITY TECHNOLOGY

725820



Note: While Convergent Connectivity Technology has made every reasonable effort to ensure the accuracy of the information in this document, Convergent Connectivity Technology does not guarantee that it is error-free, nor does Convergent Connectivity Technology make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Convergent Connectivity Technology reserves the right to make any adjustments to the information contained herein at any time without notice. Convergent Connectivity Technology expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

this specification	constitutes that you have read and agreed to a sheet and upon confirmation of your order; non-cancelable and non-returnable.
Signature:	
Company:	
Date:	

Issue Date: February '24

THE STRONGEST LINK IN YOUR SUPPLY CHAIN



PHONE: 866-905-6744 FAX: 845-651-3564

PO BOX 454 FLORIDA, NY 10921