

PRODUCT SPECIFICATIONS

CONVERGENT CONNECTIVITY TECHNOLOGY

WB105PVC



Description:	18/2 Stranded bare copper conductors PVC insulated, unshielded and wrapped with a water-blocking tape and overall PVC
Ratings/Approvals:	ETL Listed CM, RoHS Compliant
Applications:	Communication Cable, Indoor and Outdoor, Suitable for Use in Underground Application in Conduit

CONSTRUCTION

Conductor: Stranding: Insulation Material: Insulation Thickness: Number of Conductors or Pairs: Tape: Jacket Material and Color: Jacket Thickness: Overall Cable Diameter: Approx Cable Weight /1,000 ft.: Print Legend: 18 AWG Bare Copper 7 Strand Polyvinyl Chloride 0.010 in. (0.254 mm.) Nominal 2 Conductor Water Blocking Tape PVC, Black UV resistant 0.025 in. (0.635 mm.) Nominal 0.203 in. (5.156 mm.) Nominal 16.5 lbs. 3147706 CM C(ETL)US 2C/18...INDOOR/ OUTDOOR SUN /MOISTURE RES ROHS MADE IN USA

ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage: Insulation Colors: DC Resistance per Conductor @ 20°C: Min. Bend Radius (Installation): Temperature Rating:

300 V, RMS Black, Red 6.54Ω/1m' 2.50 in. -20°C to +60°C

Issue Date: January '24 Revision: 1

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744 FAX: 845-651-3564

techsupport@cctcable.com

PO BOX 454 FLORIDA, NY 10921

1



PRODUCT SPECIFICATIONS

WB105PVC



CONVERGENT CONNECTIVITY TECHNOLOGY

Note: While Convergent Connectivity Technology has made every reasonable effort to ensure the accuracy of the information in this document, Convergent Connectivity Technology does not guarantee that it is error-free, nor does Convergent Connectivity Technology make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Convergent Connectivity Technology reserves the right to make any adjustments to the information contained herein at any time without notice. Convergent Connectivity Technology expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature:

Company:

Date:

Issue Date: January '24 Revision: 1

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744 FAX: 845-651-3564 PO BOX 454 FLORIDA, NY 10921

techsupport@cctcable.com

2