

CONVERGENT CONNECTIVITY *TECHNOLOGY*

WB1003PVC

22/6 Stranded bare copper conductors PVC insulated, shield-**Description:**

ed and wrapped with a water-blocking tape and overall PVC

ETL Listed CM, RoHS Compliant Ratings/Approvals:

Applications: Communication Cable, Indoor and Outdoor, Suitable for Use

in Underground Application in Conduit



CONSTRUCTION

Conductor: 22 AWG Bare Copper

Stranding: 7 Strand

Insulation Material: Polyvinyl Chloride

Insulation Thickness: 0.010 in. (0.254 mm.) Nominal

Number of Conductors or Pairs: 6 Conductor

Shielding: Aluminum/ Polyester tape

Drain Wire: 24AWG Stranded Tin Copper

Tape: Water Blocking Tape

Jacket Material and Color: PVC, Black UV Resistant

0.025 in. Nominal Jacket Thickness:

0.225 in. Nominal Overall Cable Diameter:

Approx Cable Weight /1,000 ft.: 301bs.

Print Legend: 3147706 CM C(ETL)US 6C/22...INDOOR/

OUTDOOR SUN / MOISTURE RES

ROHS MADE IN USA

ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage: 300 V, RMS

Insulation Colors: Black, Red, White, Green,

Brown, Blue

DC Resistance per Conductor @ 20°C: $17.5\Omega/1\text{m}$

Min. Bend Radius (Installation): 3.25 in.

Temperature Rating: -20° C to $+60^{\circ}$ C

Date: January '24 Rev. 0

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744 Page 1 of 1 **PO BOX 454** FLORIDA, NY 10921 FAX: 845-651-3564

techsupport@cctcable.com

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.



CONVERGENT CONNECTIVITY TECHNOLOGY

WB1003PVC



Note: While Convergent Connectivity Technology has made every reasonable effort to ensure the accuracy of the information in this document, Convergent Connectivity Technology does not guarantee that it is error-free, nor does Convergent Connectivity Technology make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Convergent Connectivity Technology reserves the right to make any adjustments to the information contained herein at any time without notice. Convergent Connectivity Technology expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

this specification	n sheet and upon confirmation of your order; non-cancelable and non-returnable.
Signature:	
Company:	
Date:	

Date: January '24 Rev. 0

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744 FAX: 845-651-3564

Page 1 of 1

PO BOX 454 FLORIDA, NY 10921

techsupport@cctcable.com

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.