



## PRODUCT SPECIFICATIONS

**CONVERGENT  
CONNECTIVITY  
TECHNOLOGY**

### 4003

<b>Description:</b>	18/6 Solid bare copper conductors, unshielded with an overall jacket
<b>Ratings/Approvals:</b>	NEC Article 760, UL Subject 1424, Type FPLR, (ETL)US, RoHS Compliant
<b>Applications:</b>	Fire Protective Signaling Circuit Applications

---

### CONSTRUCTION

Conductor:	18 AWG Bare Copper
Stranding:	Solid
Insulation Material:	Polyvinyl Chloride
Insulation Thickness:	0.010 in. (0.254 mm.) Nominal
Number of Conductors or Pairs:	6 Conductor
Shield:	N/A
Drain:	N/A
Jacket Material:	Polyvinyl Chloride
Jacket Thickness:	0.015 in. (0.381 mm.) Nominal
Overall Cable Diameter:	0.210 in. (5.080 mm.) Nominal
Approx Cable Weight /1,000 ft.:	58 Lbs.

---

### ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage:	300 V, RMS
Insulation Colors:	Black, Red, Green, White, Brown, Blue
Temperature Rating:	-20°C to 60°C
Jacket Color:	Red or Per Customer Requirement

Issue Date: April '16      Revision: 0

***THE STRONGEST LINK IN YOUR SUPPLY CHAIN***

PHONE: 866-905-6744  
FAX: 845-651-3564

[techsupport@cctcable.com](mailto:techsupport@cctcable.com)



PO BOX 454  
FLORIDA, NY 10921



## PRODUCT SPECIFICATIONS

**CONVERGENT  
CONNECTIVITY  
TECHNOLOGY**

**4003**

**Note:** While Convergent Connectivity Technology has made every reasonable effort to ensure the accuracy of the information in this document, Convergent Connectivity Technology does not guarantee that it is error-free, nor does Convergent Connectivity Technology make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Convergent Connectivity Technology reserves the right to make any adjustments to the information contained herein at any time without notice. Convergent Connectivity Technology expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature: \_\_\_\_\_

Company: \_\_\_\_\_

Date: \_\_\_\_\_

Issue Date: April '16      Revision: 0

***THE STRONGEST LINK IN YOUR SUPPLY CHAIN***

PHONE: 866-905-6744  
FAX: 845-651-3564

[techsupport@cctcable.com](mailto:techsupport@cctcable.com)



PO BOX 454  
FLORIDA, NY 10921