



PRODUCT SPECIFICATIONS

**CONVERGENT
CONNECTIVITY
TECHNOLOGY**

4006

| | |
|---------------------------|--|
| Description: | 16/4 Solid bare copper conductors, unshielded with an overall jacket |
| Ratings/Approvals: | NEC Article 760, UL Subject 1424, Type FPLR, (ETL)US, RoHS Compliant |
| Applications: | Fire Protective Signaling Circuit Applications |

CONSTRUCTION

| | |
|---------------------------------|-------------------------------|
| Conductor: | 16 AWG Bare Copper |
| Stranding: | Solid |
| Insulation Material: | Polyvinyl Chloride |
| Insulation Thickness: | 0.010 in. (0.254 mm.) Nominal |
| Number of Conductors or Pairs: | 4 Conductor |
| Shield: | N/A |
| Drain: | N/A |
| Jacket Material: | Polyvinyl Chloride |
| Jacket Thickness: | 0.015 in. (0.381 mm.) Nominal |
| Overall Cable Diameter: | 0.200 in. (5.080 mm.) Nominal |
| Approx Cable Weight /1,000 ft.: | 43 Lbs. |

ELECTRICAL & PHYSICAL PROPERTIES

| | |
|---------------------|---------------------------------|
| Operative Voltage: | 300 V, RMS |
| Insulation Colors: | Black, Red, Green, White |
| Temperature Rating: | -20°C to 60°C |
| Jacket Color: | Red or Per Customer Requirement |

Issue Date: March '13 Revision: 0



THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744
FAX: 845-651-3564

Page 1 of 1

PO BOX 454
FLORIDA, NY 10921

techsupport@cctcable.com

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.