



## PRODUCT SPECIFICATIONS

**CONVERGENT  
CONNECTIVITY  
TECHNOLOGY**

### 4010

<b>Description:</b>	16/4 Solid bare copper conductors, unshielded with an overall jacket
<b>Ratings/Approvals:</b>	NEC Article 760, UL Subject 1424, Type FPLP, (ETL)US, RoHS Compliant
<b>Applications:</b>	Fire Protective Signaling Circuit Applications

### CONSTRUCTION

Conductor:	16 AWG Bare Copper
Stranding:	Solid
Insulation Material:	Flame Retardant Polyvinyl Chloride
Insulation Thickness:	0.010 in. (0.254 mm.) Nominal
Number of Conductors or Pairs:	4 Conductor
Shield:	None
Drain:	None
Jacket Material:	Flame Retardant Polyvinyl Chloride
Jacket Thickness:	0.015 in. (0.381 mm.) Nominal
Overall Cable Diameter:	0.200 in. (5.080 mm.) Nominal
Approx Cable Weight /1,000 ft.:	43 Lbs.

### ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage:	300 V, RMS
Insulation Colors:	Black, Red, Green, White
Temperature Rating:	-2°C to 60°C
Jacket Color:	Red or Per Customer Requirement

Issue Date: March '12      Revision: 0

**THE STRONGEST LINK IN YOUR SUPPLY CHAIN**



PHONE: 866-905-6744  
FAX: 845-651-3564

Page 1 of 1

PO BOX 454  
FLORIDA, NY 10921

[techsupport@cctcable.com](mailto:techsupport@cctcable.com)

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.