



PRODUCT SPECIFICATIONS

**CONVERGENT
CONNECTIVITY
TECHNOLOGY**

4017

Description:	14/4 Solid bare copper conductors, shielded with an overall jacket
Ratings/Approvals:	NEC Article 760, UL Subject 1424, Type FPLR, (ETL)US, RoHS Compliant
Applications:	Fire Protective Signaling Circuit Applications

CONSTRUCTION

Conductor:	14 AWG Bare Copper
Stranding:	Solid
Insulation Material:	Polyvinyl Chloride
Insulation Thickness:	0.014 in. (0.355 mm.) Nominal
Number of Conductors or Pairs:	4 Conductor
Nominal Cable Lay:	5.0 in. Left Hand Lay
Shield:	Aluminum/Polyester Tape (100% Coverage)
Drain:	Solid Tin Copper
Jacket Material:	Polyvinyl Chloride
Jacket Thickness:	0.020 in. (0.508 mm.) Nominal
Overall Cable Diameter:	0.266 in. (6.756 mm.) Nominal
Approx Cable Weight /1,000 ft.:	74 Lbs.

ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage:	300 V, RMS
Insulation Colors:	Black, Red, Green, White
Temperature Rating:	-20°C to 60°C
Jacket Color:	Red or Per Customer Requirement

Issue Date: September '12 Revision: 1



THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744
FAX: 845-651-3564

Page 1 of 1

PO BOX 454
FLORIDA, NY 10921

techsupport@cctcable.com

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.