



PRODUCT SPECIFICATIONS

**CONVERGENT
CONNECTIVITY
TECHNOLOGY**

5206

Description: Dual 18AWG solid bare copperweld RG6/U 75Ohm coaxial cable in a siamese construction

Ratings/Approvals: NEC Article 800 & 820, UL Subject 444 & 1581, Type CM/CATV, C(ETL)US, RoHs Compliant

Applications: Video Display, Point-Of-Sale Terminals, Local Area Network Controls, and CATV Broadcast Applications, Swept to 3.0 GHz.

CONSTRUCTION

Conductor: 18 AWG Bare Copperweld

Stranding: Solid

Dielectric Material: Cellular Polyethylene

Dielectric Core Diameter: 0.180 in. (4.572 mm.) Nominal

1st Shield: Coaxial Shielding Tape (100% Coverage)

2nd Shield: Aluminum Braid

Jacket Material: Polyvinyl Chloride

Nominal Overall Cable Dimensions: Minor (Coax): 0.270 in. (6.858 mm.)
Major: 0.565 in. (14.351 mm)

Approx Cable Weight /1,000 ft.: 65 lbs.

ELECTRICAL & PHYSICAL PROPERTIES

Capacitance: 16.2pF/ft Nominal

Velocity of propagation: 84% Nominal

Characteristic Impedance: 75Ω Nominal

Nominal attenuation per 100ft:

1.46 dB @ 50 MHz	7.50 dB @ 1200 MHz
2.05 dB @ 100 MHz	8.50 dB @ 1450 MHz
2.83 dB @ 200 MHz	9.50 dB @ 2200 MHz
6.88 dB @ 1000 MHz	12.0 dB @ 3000 MHz

Temperature Rating: -10°C to 60°C

Issue Date: August '13

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744
FAX: 845-651-3564

Page 1 of 1

techsupport@cctcable.com



PO BOX 454
FLORIDA, NY 10921

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.