

## PRODUCT SPECIFICATIONS

CONVERGENT CONNECTIVITY TECHNOLOGY

7252109

**Description:** 20/2 Stranded bare copper conductors, unshielded with an overall jacket

Ratings/Approvals: NEC Article 800, UL Subject 444, Type CMP, C(ETL)US, RoHS Compliant

**Applications:** Intercom Systems, Security Systems, Sound and Audio, Background Music, and

Power-Limited Control Circuits. Indoor Applications

## CONSTRUCTION

Conductor: 20 AWG Bare Copper

Stranding: 7 Strand

Insulation Material: Low Smoke Flame Retardant Polyvinyl Chloride

Insulation Thickness: 0.007 in. (0.177 mm.) Nominal

Number of Conductors or Pairs: 2 Conductor

Shield: N/A

Drain: N/A

Jacket Material: Low Smoke Flame Retardant Polyvinyl Chloride

Jacket Thickness: 0.015 in. (0.381 mm.) Nominal

Overall Cable Diameter: 0.130 in. (3.302 mm.) Nominal

Approx Cable Weight /1,000 ft.:

## **ELECTRICAL & PHYSICAL PROPERTIES**

Operative Voltage: 300 V RMS Insulation Colors: Black, Red Temperature Rating:  $-2^{\circ}\text{C to } +60^{\circ}\text{C}$ 

Issue Date: August '16 Revision: 2

THE STRONGEST LINK IN YOUR SUPPLY CHAIN



PHONE: 866-905-6744 FAX: 845-651-3564

PO BOX 454 FLORIDA, NY 10921



**CONVERGENT CONNECTIVITY TECHNOLOGY** 

7252109

**Note:** While Convergent Connectivity Technology has made every reasonable effort to ensure the accuracy of the information in this document, Convergent Connectivity Technology does not guarantee that it is error-free, nor does Convergent Connectivity Technology make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Convergent Connectivity Technology reserves the right to make any adjustments to the information contained herein at any time without notice. Convergent Connectivity Technology expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.	
Signature:	
Company:	
Date:	

Your signature constitutes that you have read and agreed to

Revision: 2 Issue Date: August '16

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

**RoHS**<sup>∜</sup>

PHONE: 866-905-6744 FAX: 845-651-3564

**PO BOX 454** FLORIDA, NY 10921