



PRODUCT SPECIFICATIONS

CONVERGENT
CONNECTIVITY
TECHNOLOGY

725116



Description:

All in one design for Access Control with individual components designed for specific applications.

Ratings/Approvals:

NEC Article 800, UL Subject 444, Type CMP, C(ETL)US, RoHS Compliant

Applications:

Power Lock, Card Reader, Door Contact and Rex/Spare

CONSTRUCTION

Component 1:

Conductor:	18 AWG Bare Copper
Stranding:	7 Strand
Insulation Material:	Low Smoke Flame Retardant PVC
Insulation Color:	Black, Red, Green, White
Number of Conductors or Pairs:	4 Conductor
Shield:	N/A
Drain:	N/A
Jacket Material:	Low Smoke Flame Retardant PVC
Jacket Color:	Gray
Overall Jacket Diameter:	0.179 in. (4.546 mm.) Nominal
Surface Print:	POWER LOCK CMP 4/18AWG C(ETL)US A B C D E 0 1 2 3 4 5 6 7 8 9



Component 2:

Conductor:	22 AWG Bare Copper
Stranding:	7 Strand
Insulation Material:	Low Smoke Flame Retardant PVC
Insulation Color:	Black/Red, Green/ White, Orange/Brown
Number of Conductors or Pairs:	6 Conductor (3 Pairs)
Shield:	Aluminum/Polyester Tape (100% Coverage)
Drain:	Stranded Tin Copper
Jacket Material:	Low Smoke Flame Retardant PVC
Jacket Color:	Orange
Overall Jacket Diameter:	0.200 in. (5.080 mm.) Nominal
Surface Print:	CARD READER CMP 3P/22AWG C(ETL)US A B C D E 0 1 2 3 4 5 6 7 8 9



Issue Date: October '12 Revision: 4

THE STRONGEST LINK IN YOUR SUPPLY CHAIN



PHONE: 866-905-6744
FAX: 845-651-3564

Page 1 of 2

PO BOX 454
FLORIDA, NY 10921

techsupport@cctcable.com

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.



PRODUCT SPECIFICATIONS

**CONVERGENT
CONNECTIVITY
TECHNOLOGY**

725116

Component 3:

Conductor:	22 AWG Bare Copper
Stranding:	7 Strand
Insulation Material:	Low Smoke Flame Retardant PVC
Insulation Color:	Black, Red
Number of Conductors or Pairs:	2 Conductor
Shield:	N/A
Drain:	N/A
Jacket Material:	Low Smoke Flame Retardant PVC
Jacket Color:	White
Overall Jacket Diameter:	0.122 in. (3.098 mm.) Nominal
Surface Print:	DOOR CONTACT CMP 2/22AWG C(ETL)US A B C D E 0 1 2 3 4 5 6 7 8 9



Component 4:

Conductor:	22 AWG Bare Copper
Stranding:	7 Strand
Insulation Material:	Low Smoke Flame Retardant PVC
Insulation Color:	Black, Red, Green, White
Number of Conductors or Pairs:	4 Conductor
Shield:	N/A
Drain:	N/A
Jacket Material:	Low Smoke Flame Retardant PVC
Jacket Color:	Blue
Overall Jacket Diameter:	0.140 in. (3.556 mm.) Nominal
Surface Print:	REX/SPARE CMP 4/22AWG C(ETL)US A B C D E 0 1 2 3 4 5 6 7 8 9



Overall Cable:

Jacket Material:	Low Smoke Flame Retardant PVC
Jacket Color:	Yellow
Overall Jacket Diameter:	0.410 in. (10.414 mm.) Nominal
Surface Print:	ACCESS CONTROL CABLE CMP 4/18AWG 12/22AWG C(ETL)US + Sequential Footage Marking

Issue Date: October '12 Revision: 4

THE STRONGEST LINK IN YOUR SUPPLY CHAIN



PHONE: 866-905-6744
FAX: 845-651-3564

Page 2 of 2

PO BOX 454
FLORIDA, NY 10921

techsupport@cctcable.com

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.