



# PRODUCT SPECIFICATIONS

**CONVERGENT  
CONNECTIVITY  
TECHNOLOGY**

**725122**



- Description:** 14/4 Stranded bare copper conductors, unshielded with an overall jacket
- Ratings/Approvals:** NEC Article 725, UL Subject 13, Type CL2P FT6, (ETL)US, RoHS Compliant
- Applications:** Intercom Systems, Security Systems, Sound and Audio, Background Music, and Power-Limited Control Circuits. Indoor Applications

## CONSTRUCTION

Conductor:	14 AWG Bare Copper
Stranding:	7 Strand
Insulation Material:	Plenum Polymer
Insulation Thickness:	0.009 in. (0.228 mm.) Nominal
Number of Conductors or Pairs:	4 Conductor
Shield:	N/A
Drain:	N/A
Jacket Material:	Plenum Polymer
Jacket Thickness:	0.015 in. (0.381 mm.) Nominal
Overall Cable Diameter:	0.247 in. (6.273 mm.) Nominal
Approx Cable Weight /1,000 ft.:	72 lbs.

## ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage:	150 V, RMS
Insulation Colors:	Black, Red, White, Green
DC Resistance per Conductor @ 20°C:	2.6Ω/1m'
Maximum Pulling Tension:	168 lbs
Min. Bend Radius (Installation):	2.6 in.

Issue Date: November '09

**THE STRONGEST LINK IN YOUR SUPPLY CHAIN**



PHONE: 866-905-6744  
FAX: 845-651-3564

Page 1 of 1

PO BOX 454  
FLORIDA, NY 10921

[techsupport@cctcable.com](mailto:techsupport@cctcable.com)

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.