

PRODUCT SPECIFICATIONS

CONVERGENT CONNECTIVITY TECHNOLOGY

725201

Description: 22/2 Stranded bare copper conductors, shielded with an overall jacket

Ratings/Approvals: NEC Article 800, UL Subject 444, Type CMP, C(ETL)US, RoHS Compliant

Applications: Intercom Systems, Security Systems, Sound and Audio, Background Music, and

Power-Limited Control Circuits. Indoor Applications

CONSTRUCTION

Conductor: 22 AWG Bare Copper

Stranding: 7 Strand

Insulation Material: Low Smoke Flame Retardant Polyvinyl Chloride

Insulation Thickness: 0.007 in. (0.177 mm.) Nominal

Number of Conductors or Pairs: 2 Conductor

Shield: Aluminum/Polyester Tape (100% Coverage)

Drain: Stranded Tin Copper

Jacket Material: Low Smoke Flame Retardant Polyvinyl Chloride

Jacket Thickness: 0.015 in. (0.381 mm.) Nominal

Overall Cable Diameter: 0.120 in. (3.048 mm.) Nominal

Approx Cable Weight /1,000 ft.:

ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage: 300 V RMS Insulation Colors: Black, Red Temperature Rating: $-2^{\circ}\text{C to } +60^{\circ}\text{C}$

Issue Date: August '16 Revision: 2

THE STRONGEST LINK IN YOUR SUPPLY CHAIN



PHONE: 866-905-6744 FAX: 845-651-3564

PO BOX 454 FLORIDA, NY 10921



PRODUCT SPECIFICATIONS

CONVERGENT CONNECTIVITY TECHNOLOGY

725201



Note: While Convergent Connectivity Technology has made every reasonable effort to ensure the accuracy of the information in this document, Convergent Connectivity Technology does not guarantee that it is error-free, nor does Convergent Connectivity Technology make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Convergent Connectivity Technology reserves the right to make any adjustments to the information contained herein at any time without notice. Convergent Connectivity Technology expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.	
Signature:	
Company:	
Date:	

Your signature constitutes that you have read and agreed to

Issue Date: August '16 Revision: 2

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

RoHS ∜ c Usus

PHONE: 866-905-6744 FAX: 845-651-3564

PO BOX 454 FLORIDA, NY 10921