



PRODUCT SPECIFICATIONS

**CONVERGENT
CONNECTIVITY
TECHNOLOGY**

725203

- Description:** 18/2 Stranded bare copper conductors, shielded with an overall jacket
- Ratings/Approvals:** NEC Article 800, UL Subject 444, Type CMP, C(ETL)US, RoHS Compliant
- Applications:** Intercom Systems, Security Systems, Sound and Audio, Background Music, and Power-Limited Control Circuits. Indoor Applications

CONSTRUCTION

Conductor:	18 AWG Bare Copper
Stranding:	7 Strand
Insulation Material:	Low Smoke PVC
Insulation Thickness:	0.007 in. (0.177 mm.) Nominal
Number of Conductors or Pairs:	2 Conductor
Shield:	Aluminum/Polyester Tape(100% Coverage)
Drain:	Stranded Tin Copper
Jacket Material:	Low Smoke PVC
Jacket Thickness:	0.015 in. (0.381 mm.) Nominal
Overall Cable Diameter:	0.154 in. (3.911 mm.) Nominal
Approx Cable Weight /1,000 ft.:	20 lbs.

ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage:	300 V RMS
Insulation Colors:	Black, Red
DC Resistance per Conductor @ 20°C:	6.6Ω/1m'
Temperature Rating:	-2°C to +60°C

Issue Date: September '15

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744
FAX: 845-651-3564

techsupport@cctcable.com



PO BOX 454
FLORIDA, NY 10921



PRODUCT SPECIFICATIONS

*CONVERGENT
CONNECTIVITY
TECHNOLOGY*

725203



Note: While Convergent Connectivity Technology has made every reasonable effort to ensure the accuracy of the information in this document, Convergent Connectivity Technology does not guarantee that it is error-free, nor does Convergent Connectivity Technology make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Convergent Connectivity Technology reserves the right to make any adjustments to the information contained herein at any time without notice. Convergent Connectivity Technology expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature: _____

Company: _____

Date: _____

Issue Date: September '15

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744
FAX: 845-651-3564

techsupport@cctcable.com



PO BOX 454
FLORIDA, NY 10921