

CONVERGENT CONNECTIVITY TECHNOLOGY

725209

Description:	22/4 Stranded bare copper conductors, shielded with an overall jacket
Ratings/Approvals:	NEC Article 800, UL Subject 444, Type CMP, C(ETL)US, RoHS Compliant
Applications:	Intercom Systems, Security Systems, Sound and Audio, Background Music, and Power-Limited Control Circuits. Indoor Applications

CONSTRUCTION

Conductor:	22 AWG Bare Copper
Stranding:	7 Strand
Insulation Material:	Low Smoke Flame Retardant Polyvinyl Chloride
Insulation Thickness:	0.007 in. (0.177 mm.) Nominal
Number of Conductors or Pairs:	4 Conductor
Shield:	Aluminum/Polyester Tape (100% Coverage)
Drain:	Stranded Tin Copper
Jacket Material:	Low Smoke Flame Retardant Polyvinyl Chloride
Jacket Thickness:	0.015 in. (0.381 mm.) Nominal
Overall Cable Diameter:	0.137 in. (3.479 mm.) Nominal
Approx Cable Weight /1,000 ft.:	17 lbs.

ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage:
Insulation Colors:
Temperature Rating:

300 V RMS Black, Natural, Red, Green -2° C to $+60^{\circ}$ C

Issue Date: June '15

Revision: 1

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

RoHS《

PO BOX 454 FLORIDA, NY 10921

1

PHONE: 866-905-6744 FAX: 845-651-3564

techsupport@cctcable.com



PRODUCT SPECIFICATIONS

CONVERGENT CONNECTIVITY TECHNOLOGY

725209

Note: While Convergent Connectivity Technology has made every reasonable effort to ensure the accuracy of the information in this document, Convergent Connectivity Technology does not guarantee that it is error-free, nor does Convergent Connectivity Technology make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Convergent Connectivity Technology reserves the right to make any adjustments to the information contained herein at any time without notice. Convergent Connectivity Technology expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature:

Company:

Date:

Issue Date: June '15

Revision: 1



THE STRONGEST LINK IN YOUR SUPPLY CHAIN **ROHS**

PHONE: 866-905-6744 FAX: 845-651-3564 PO BOX 454 FLORIDA, NY 10921 2

techsupport@cctcable.com