



PRODUCT SPECIFICATIONS

**CONVERGENT
CONNECTIVITY
TECHNOLOGY**

7253512

Description: 22/12 Pair Stranded bare copper conductors, individually shielded with an overall jacket

Ratings/Approvals: NEC Article 800, UL Subject 444, Type CMP, C(ETL)US, RoHS Compliant

Applications: Intercom Systems, Security Systems, Sound and Audio, Background Music, and Power-Limited Control Circuits. Indoor Applications

CONSTRUCTION

Conductor:	22 AWG Bare Copper
Stranding:	7 Strand
Insulation Material:	Plenum Polymer
Insulation Thickness:	0.008 in. (0.203 mm) Nominal
Number of Conductors or Pairs:	12 Pairs
Individual Shield:	Aluminum/Polyester Tape(100% Coverage)
Individual Drain:	Stranded Tin Copper
Jacket Material:	Plenum Polymer
Jacket Thickness:	0.018 in. (0.457 mm) Nominal
Overall Cable Diameter:	0.355 in. (9.017 mm) Nominal
Approx Cable Weight /1,000 ft.:	105 lbs.

ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage:	300 V, RMS
Insulation Colors:	Black paired with Red Black paired with White Black paired with Green Black paired with Blue Black paired with Yellow Black paired with Brown Black paired with Orange Red paired with White Red paired with Green Red paired with Blue Red paired with Yellow Red paired with Brown
Temperature Rating:	-2°C to + 60°C

Issue Date: February '11 Revision: 0

THE STRONGEST LINK IN YOUR SUPPLY CHAIN



PHONE: 866-905-6744
FAX: 845-651-3564

Page 1 of 1

PO BOX 454
FLORIDA, NY 10921

techsupport@cctcable.com

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.