



PRODUCT SPECIFICATIONS

**CONVERGENT
CONNECTIVITY
TECHNOLOGY**

725216

Description:	16/4 Stranded bare copper conductors, shielded with an overall jacket
Ratings/Approvals:	NEC Article 800, UL Subject 444, Type CMP, C(ETL)US, RoHS Compliant
Applications:	Intercom Systems, Security Systems, Sound and Audio, Background Music, and Power-Limited Control Circuits. Indoor Applications

CONSTRUCTION

Conductor:	16 AWG Bare Copper
Stranding:	7 Strand
Insulation Material:	Low Smoke Flame Retardant Polyvinyl Chloride
Insulation Thickness:	0.007 in. (0.177 mm.) Nominal
Number of Conductors or Pairs:	4 Conductor
Shield:	Aluminum/Polyester Tape (100% Coverage)
Drain:	Stranded Tin Copper
Jacket Material:	Low Smoke Flame Retardant Polyvinyl Chloride
Jacket Thickness:	0.015 in. (0.381 mm.) Nominal
Overall Cable Diameter:	0.207 in. (5.257 mm.) Nominal
Approx Cable Weight /1,000 ft.:	48 lbs.

ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage:	300 V RMS
Insulation Colors:	Black, Natural, Red, Green
Temperature Rating:	-2°C to +60°C

Issue Date: October '10 Revision: 0

THE STRONGEST LINK IN YOUR SUPPLY CHAIN



PHONE: 866-905-6744
FAX: 845-651-3564

Page 1 of 1

PO BOX 454
FLORIDA, NY 10921

techsupport@cctcable.com

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.