



PRODUCT SPECIFICATIONS

**CONVERGENT
CONNECTIVITY
TECHNOLOGY**

725356

Description: 22/6 Pair Stranded bare copper conductors, individually shielded with an overall jacket

Ratings/Approvals: NEC Article 800, UL Subject 444, Type CMP, C(ETL)US, RoHS Compliant

Applications: Intercom Systems, Security Systems, Sound and Audio, Background Music, and Power-Limited Control Circuits. Indoor Applications

CONSTRUCTION

| | |
|---------------------------------|--|
| Conductor: | 22 AWG Bare Copper |
| Stranding: | 7 Strand |
| Insulation Material: | Plenum Polymer |
| Insulation Thickness: | 0.008 in. (0.203 mm) Nominal |
| Number of Conductors or Pairs: | 6 Pairs |
| Individual Shield: | Aluminum/Polyester Tape(100% Coverage) |
| Individual Drain: | Stranded Tin Copper |
| Jacket Material: | Plenum Polymer |
| Jacket Thickness: | 0.018 in. (0.457 mm) Nominal |
| Overall Cable Diameter: | 0.286 in. (7.264 mm) Nominal |
| Approx Cable Weight /1,000 ft.: | 61 lbs. |

ELECTRICAL & PHYSICAL PROPERTIES

| | |
|---------------------|--|
| Operative Voltage: | 300 V, RMS |
| Insulation Colors: | Black paired with Red Black paired with White Black paired with Green Black paired with Blue Black paired with Yellow Black paired with Brown |
| Temperature Rating: | -2°C to + 60°C |

Issue Date: February '11 Revision: 0

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744
FAX: 845-651-3564

Page 1 of 1

techsupport@cctcable.com



PO BOX 454
FLORIDA, NY 10921

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.