



PRODUCT SPECIFICATIONS

**CONVERGENT
CONNECTIVITY
TECHNOLOGY**

725359

Description: 22/9 Pair Stranded bare copper conductors, individually shielded with an overall jacket

Ratings/Approvals: NEC Article 800, UL Subject 444, Type CMP, C(ETL)US, RoHS Compliant

Applications: Intercom Systems, Security Systems, Sound and Audio, Background Music, and Power-Limited Control Circuits. Indoor Applications

CONSTRUCTION

Conductor: 22 AWG Bare Copper

Stranding: 7 Strand

Insulation Material: Plenum Polymer

Insulation Thickness: 0.008 in. (0.203 mm) Nominal

Number of Conductors or Pairs: 9 Pairs

Individual Shield: Aluminum/Polyester Tape(100% Coverage)

Individual Drain: Stranded Tin Copper

Jacket Material: Plenum Polymer

Jacket Thickness: 0.018 in. (0.457 mm) Nominal

Overall Cable Diameter: 0.338 in. (8.585 mm) Nominal

Approx Cable Weight /1,000 ft.: 89 lbs.

ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage: 300 V, RMS

Insulation Colors: Black paired with Red
Black paired with White
Black paired with Green
Black paired with Blue
Black paired with Yellow
Black paired with Brown
Black paired with Orange
Red paired with White
Red paired with Green

Temperature Rating: -2°C to + 60°C

Issue Date: February '11 Revision: 0

THE STRONGEST LINK IN YOUR SUPPLY CHAIN



PHONE: 866-905-6744
FAX: 845-651-3564

Page 1 of 1

PO BOX 454
FLORIDA, NY 10921

techsupport@cctcable.com

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.