



TIGHT BUFFER OFNR CABLES PRODUCT SPECIFICATION 77XXX22JAZSXNF

This document establishes the specification requirements for a distribution fiber optic cable. This cable construction consists of multimode fibers in a distribution tight-buffered design with a riser rated PVC jacket. It contains test values for all-important mechanical, optical, and environmental parameters and as such, is the basis for all-incoming inspection and acceptance.

1.0 OVERALL CABLE CONSTRUCTION

1.1 Tight Buffered Fiber

Dimension: 900µm, nominal.

Tight buffered fiber color code: 1-blue, 2-orange, 3-green, 4-brown, 5-slate, 6-white, 7-red, 8-black, 9-yellow, 10-violet, 11-rose, and 12-aqua.

1.2 Sub-unit consists of aramid yarns that are pulled in with the tight-buffered fibers under a sub-unit jacket.

1.3 Cable strength Member

Fiberglass Epoxy Rod (dielectric)

An up coat of PVC (if necessary per construction for symmetry)

1.4 Cable Core

Sub-units and fillers (if needed) are stranded around the CSM, using reverse oscillation.

A non-wicking and non-hygroscopic tape is applied longitudinally with a nominal 25% overlap.

Binder yarns are applied over the core tape.

1.5 Outer Sheath

Orange riser rated PVC jacket (or color per customer request)

1.6 Cable Markings

Indent printed: CCT GROUP77, FIBER OPTIC CABLE, # of fibers-62.5/125, MM/YY (month and year of manufacture), OFNP C(ETL)US sequentially meter marked. Special print as required by customer.

1.7 Nominal Cable Dimensions & Weights

CCT Part Number	No. of Fibers	Cable OD (mm)	Cable OD (in.)	Weight KG/KM	Weight LB/1000ft
7701822JAZSFNF	18	13.9	0.546	155	104
7702422JAZSFNF	24	13.9	0.546	151	101
7703622JAZSFNF	36	16.9	0.666	230	155
7704822JAZSLNF	48	16.1	0.634	201	135
7706022JAZSLNF	60	17.7	0.696	246	165
7707222JAZSLNF	72	19.2	0.756	304	204
7709622JAZSLNF	96	23.5	0.926	471	316
7714422JAZSLNF	144	27.4	1.078	580	390



2.0 FIBER CHARACTERISTICS - Physical Parameters (nominal)

<u>Fiber Type</u>	<u>Multimode Graded Index</u>
Maximum Attenuation @ 850/1300nm	3.2 /1.0 dB/km
Minimum Bandwidth @850/1300nm	200/600MHz-km
Core Diameter, nominal	62.5 ± 3 µm
Cladding Diameter	125.0 ± 1.0 µm
Primary Coating Diameter	245 ± 10 µm
Cladding Non-circularity	<2%
Core/Clad Offset	3 µm
Zero Dispersion Wavelength	1320-1365nm
Numerical Aperture	0.275 ± .015
Group Refractive Index @ 850/1300nm	1.496/1.491
Proof Test	100 kpsi

**Guaranteed Gigabit Ethernet Distance of 300/550mtr per IEEE802.3z.*

**Measured attenuations on shipping reels will not exceed the nominal values by .75dB/km.*

3.0 MECHANICAL & ENVIRONMENTAL PERFORMANCE

Maximum Tensile Load for:	Impact Resistance: 25 Impacts (min.)
Installation: 2700N / 607lbf	Flexing, ±90°: 25 Cycles (min.)
Long Term: 890N / 200lbf	Temperature Rating:
Minimum bending radius:	Operation: -40°C to +85°C
Loaded: 20 x diameter	Installation: 0°C to +75°C
Unloaded: 10 x diameter	Storage: -55°C to +85°C
Crush Resistance: 220N/cm	

4.0 PREPARATION FOR DELIVERY

The cable shall be packaged to preclude the inducement of damage due to handling and transportation, and shall be in accordance with the best commercial practices available.

5.0 APPLICABLE DOCUMENTS

Reference Documents:	TIA/EIA FOTP Standards 455
	Color Coding of Fiber Optic Cables TIA/EIA-598
	UL 1666
	GR-409-CORE