



PRODUCT SPECIFICATIONS

CONVERGENT
CONNECTIVITY
TECHNOLOGY

CAT3P4

- Description:** Unshielded four twisted pair Category 3 Horizontal Cable with a flame resistant low smoke PVC jacket.
- Standards/Listings:** NEC Article 800, UL Subject 444, Type CMP, C(ETL)US, RoHS Compliant
- Applications:** Supports all category 3 applications including 10BASE-T, 4/16 Mbps Token Ring, 25.6 Mbps ATM.

CONSTRUCTION

- Conductor:** 24 AWG Solid Bare Copper
- Number of Conductors or Pairs:** 4 Pair
- Jacket Material:** Flame Resistant Low Smoke Polyvinyl Chloride
- Nominal Overall Cable Diameter:** 0.166 inch (4.216 mm)
- Approximate Cable Weight:** 19 lb/1,000 ft.

ELECTRICAL & PHYSICAL PROPERTIES

- Temperature Rating:** -2°C to +60°C
- Velocity of Propagation:** 72%
- Mutual Capacitance:** 18.7 pF/ft Nominal
- Capacitance Unbalance:** 330 pF/100m maximum
- Maximum Conductor D.C.R.:** 28.6Ω/1,000 ft
- Maximum Delay Skew:** 45.0ns/100m
- Characteristic Impedance:** From 0.772 MHz — 16 MHz 100 ± 15Ω
- Insulation Colors:** White/Blue paired with Blue
White/Orange paired with Orange
White/Green paired with Green
White/Brown paired with Brown

ELECTRICAL CHARACTERISTICS

<u>Frequency</u>	<u>SRL</u>	<u>NEXT</u>	<u>Insertion Loss</u>	<u>ACR</u>
<u>MHz</u>	<u>dB</u>	<u>dB</u>	<u>dB/100 m</u>	<u>dB</u>
	<u>Minimum</u>	<u>Minimum</u>	<u>Minimum</u>	<u>Minimum</u>
1	12.0	41.3	2.6	38.7
4	12.0	32.3	5.6	26.7
8	12.0	27.8	8.5	19.3
10	12.0	26.3	9.7	16.6
16	10.0	23.2	13.1	10.1

Issue Date: April '10 Revision: 0

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744
FAX: 845-651-3564

Page 1 of 1

techsupport@cctcable.com

PO BOX 454
FLORIDA, NY 10921



The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.