



PRODUCT SPECIFICATIONS

CONVERGENT
CONNECTIVITY
TECHNOLOGY

CAT5EP4

Description:

Unshielded four twisted pair Category 5e Horizontal Cable with a flame retardant PVC jacket. Extended Testing to 350 MHz

Standards/Listings:

ANSI/TIA/EIA 568C.2 Category 5e Swept to 350 MHz, ISO/IEC 11801 Category 5e, NEC Article 800, UL 910: CMP FT6, ETL Electrically Verified to ANSI/TIA/EIA 568C.2 Category 5e, C(ETL)US CMP, RoHS Compliant

Applications:

Supports all category 5 applications including Ethernet 100BASE-TX, 100BASE-VG and 155 ATM. Particularly suited for high bandwidth applications such as 622 ATM, Wideband, and Ethernet 1000BASE-T.

CONSTRUCTION

Conductor:	24 AWG Solid Bare Copper
Number of Conductors or Pairs:	4 Pair
Jacket Material:	Flame Retardant Polyvinyl Chloride
Nominal Overall Cable Diameter:	0.185 inch (4.699 mm)
Approximate Cable Weight:	22 lb/1,000 ft.

ELECTRICAL & PHYSICAL PROPERTIES

Temperature Rating:	Installation: 0°C to 50°C Operation: -2°C to 60°C
Velocity of Propagation:	72%
Mutual Capacitance:	14 pF/ft Nominal
Capacitance Unbalance:	330 pF/ft Maximum
Maximum Conductor D.C.R.:	28.6Ω/1,000 ft
Maximum D.C.R. Unbalance:	3%
Maximum Delay Skew:	15.0ns/100m
Maximum Propagation Delay Skew:	5.7ns/100m
Characteristic Impedance:	From 0.772 MHz — 100 MHz 100 ± 15% From 100 MHz — 250 MHz 100 ± 22% From 201 MHz—350 MHz 100 ± 32%
Maximum Installing Tension:	25 lb
Minimum Bending Radius:	1.0 inch
Insulation Colors:	Blue paired with White/Blue Orange paired with White/Orange Green paired with White/Green Brown paired with White/Brown

Issue Date: March '13 Revision: 0

THE STRONGEST LINK IN YOUR SUPPLY CHAIN



PHONE: 866-905-6744
FAX: 845-651-3564

Page 1 of 2

PO BOX 454
FLORIDA, NY 10921

techsupport@cctcable.com

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.



PRODUCT SPECIFICATIONS

CONVERGENT
CONNECTIVITY
TECHNOLOGY

CAT5EP4

ELECTRICAL CHARACTERISTICS

<u>Frequency</u>	<u>SRL</u>	<u>Return Loss</u>	<u>Attenuation</u>	<u>PS-NEXT</u>	<u>NEXT</u>	<u>ELFEXT</u>	<u>PS-ELFEXT</u>
<u>MHz</u>	<u>dB</u>	<u>dB</u>	<u>dB (100m)</u>	<u>dB</u>	<u>dB</u>	<u>dB</u>	<u>dB</u>
	<u>Minimum</u>	<u>Minimum</u>	<u>Maximum</u>	<u>Minimum</u>	<u>Minimum</u>	<u>Minimum</u>	<u>Minimum</u>
1	23.0	20.0	2.0	68.3	70.3	63.8	60.8
4	23.0	20.3	4.0	59.3	61.3	51.7	48.7
10	23.0	25.0	6.4	53.3	55.3	43.8	40.8
16	23.0	25.0	8.2	50.3	52.3	39.7	36.7
20	23.0	25.0	9.2	48.8	50.8	37.7	34.7
31.25	21.5	23.6	11.7	45.9	47.9	33.9	30.9
62.5	18.1	21.5	16.9	41.4	43.4	27.8	24.8
100	16.0	20.1	21.9	38.3	40.3	23.8	20.8
250	12.0	17.3	36.8	32.3	34.3	15.8	12.8
300	11.2	16.8	40.9	31.2	33.2	14.2	11.2
350	10.6	16.3	44.8	30.2	32.2	12.9	9.9

Issue Date: March '13 Revision: 0

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744
FAX: 845-651-3564

Page 2 of 2

techsupport@cctcable.com



PO BOX 454
FLORIDA, NY 10921

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.