



PRODUCT SPECIFICATIONS

**CONVERGENT
CONNECTIVITY
TECHNOLOGY**

P5226

Description: 18AWG solid bare copper RG-6/U 75 Ohm Plenum coaxial cable and two 18AWG bare copper conductors, in a siamese construction, with an overall jacket

Ratings/Approvals: NEC Article 800, UL Subject 444, Type CMP, C(ETL)US, RoHS Compliant

Applications: CATV, Radio, Camera and Camera Control

CONSTRUCTION

Conductor (coax):	18 AWG Bare Copper	Conductor (2C):	18 AWG Bare Copper
Stranding (coax):	Solid	Stranding (2C):	7 Strand
Dielectric Material (coax):	Foamed FEP	Insulation Material (2C):	Low Smoke Flame Retardant PVC
Dielectric Core Diameter (coax):	0.176 in. (4.470 mm.) Nominal	Insulation Thickness (2C):	0.007 in. (0.228 mm.) Nominal
Braid Shield (coax):	Bare Copper Braid	Color Code (2C):	Black, Red
Overall Construction type:	Siamese		
Overall Jacket Material:	Low Smoke Flame Retardant PVC		
Nominal Overall Dimensions:	Minor over RG-6/U:	0.243 in (6.172 mm)	
	Minor over 18/2C:	0.162 in (4.114 mm)	
	Major:	0.430 in (10.922 mm)	
Approx Cable Weight/1,000ft.:	65 lbs.		

ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage:	300 V RMS
Nominal Capacitance (coax):	16.3 pF/ft
Nominal Velocity of propagation (coax):	83%
Nominal Impedance (coax):	75Ω
Nominal attenuation per 100ft (coax):	1.50 dB @ 50 MHz 2.10 dB @ 100 MHz 3.10 dB @ 200 MHz 4.50 dB @ 400 MHz
Temperature Rating:	-2°C to +60°C

Issue Date: February '13 Revision: 2

THE STRONGEST LINK IN YOUR SUPPLY CHAIN



PHONE: 866-905-6744
FAX: 845-651-3564

Page 1 of 1

PO BOX 454
FLORIDA, NY 10921

techsupport@cctcable.com

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.