



PRODUCT SPECIFICATIONS

**CONVERGENT
CONNECTIVITY
TECHNOLOGY**

RS9004

- Description:** 12/2 High Strand Audio Cable, unshielded with an Overall PVC Jacket
- Ratings/Approvals:** NEC Article 725, UL Subject 13, Type CL3R, (ETL)US, C(ETL) FT4, RoHS Compliant
- Applications:** Intercom Systems, Security Systems, Sound and Audio, Background Music, and Power-Limited Control Circuits. Indoor Applications

CONSTRUCTION

Conductor:	12 AWG Bare Copper (OF)
Stranding:	105 x 32
Insulation Material:	Polyvinyl Chloride
Insulation Thickness:	0.015 in. (0.381 mm.) Nominal
Number of Conductors or Pairs:	2Conductor
Shield:	N/A
Drain:	N/A
Jacket Material:	Polyvinyl Chloride
Jacket Thickness:	0.020 in. (0.508 mm.) Nominal
Overall Cable Diameter:	0.280 in. (7.112 mm.) Nominal
Approx Cable Weight /1,000 ft.:	65 lbs.

ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage:	150 V, RMS
Insulation Colors:	Black, Red
Temperature Rating:	-20°C to +75°C

Issue Date: August '13 Revision: 0

THE STRONGEST LINK IN YOUR SUPPLY CHAIN



PHONE: 866-905-6744
FAX: 845-651-3564

Page 1 of 1

PO BOX 454
FLORIDA, NY 10921

techsupport@cctcable.com

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.