



PRODUCT SPECIFICATIONS

**CONVERGENT
CONNECTIVITY
TECHNOLOGY**

SH2021

Description: Multi-Media Cable, Three Category 5e 350MHz cables and one RG6/U Quad Shield cable under an overall jacket.

Standards/Listings: ANSI/TIA/EIA 568C.2 Category 5e Swept to 350 MHz, ISO/EIC 11801 Category 5e, NEC Article 800, UL 1581: CM, ETL Electrically Verified to ANSI/TIA/EIA 568C.2 Category 5e, C(ETL)US CM

CONSTRUCTION

Cat5e Leg

Conductor: 24 AWG Solid Bare Copper

Number of Conductors or Pairs: 4 Pair

Insulation Colors: Blue paired with White/Blue
Orange paired with White/Orange
Brown paired with White/Brown
Green paired with White/Green

Jacket Material: Polyvinyl Chloride

Jacket Color: Blue, Yellow and White

Nominal Overall Diameter: 0.185 inch (4.699 mm)

RG6/U Quad Leg

Conductor: 18 AWG Bare Copperweld

Stranding: Solid

Dielectric Material: Cellular Polyethylene

Dielectric Core Diameter: 0.180 in. (4.572 mm.) Nominal

1st Shield: Coaxial Shielding Tape (100% Coverage)

2nd Shield: Aluminum Braid

3rd Shield: Coaxial Shielding Tape (100% Coverage)

4th Shield: Aluminum Braid

Jacket Material: Polyvinyl Chloride

Jacket Colors: Black

Nominal Overall Diameter: 0.282 in. (7.162 mm.)

Overall Cable

Construction: Three category 5e cables, one RG6/U Quad cable are cabled and overall jacketed.

Jacket Material: Polyvinyl Chloride

Jacket Color: Per Customer Requirement

Nominal Overall Cable Diameter: 0.650 in. (16.510 mm)

Surface Print: 3122598 1RG6U/18AWG QUAD SHIELD SWEPT TO 3.0 GHZ + 3CAT5E/24AWG CM C(ETL)US
+ Sequential Footage Marking

Issue Date: August '10 Revision: 0

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744
FAX: 845-651-3564

Page 1 of 3

PO BOX 454
FLORIDA, NY 10921

techsupport@cctcable.com

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.



PRODUCT SPECIFICATIONS

**CONVERGENT
CONNECTIVITY
TECHNOLOGY**

SH2021

Cat5e ELECTRICAL & PHYSICAL PROPERTIES

Temperature Rating:	Installation: 0°C to 50°C Operation: -10°C to 60°C
Velocity of Propagation:	70%
Mutual Capacitance:	14 pF/ft Nominal
Capacitance Unbalance:	330 pF/ft maximum
Maximum Conductor D.C.R.:	28.6Ω/1,000 ft
Maximum D.C.R. Unbalance:	5%
Maximum Delay Skew:	45.0ns/100m
Maximum Propagation Delay Skew:	5.7ns/100m
Characteristic Impedance:	From 0.772 MHz - 100 MHz 100 ± 15% From 100 MHz - 250 MHz 100 ± 22% From 201 MHz - 350 MHz 100 ± 32%
Maximum Installing Tension:	25 lb
Minimum Bending Radius:	1.0 inch

RG6/U Quad ELECTRICAL & PHYSICAL PROPERTIES

Capacitance:	16.2pF/ft Nominal
Velocity of propagation:	84% Nominal
Characteristic Impedance:	75Ω Nominal
Nominal attenuation per 100ft:	1.46 dB @ 50 MHz 2.05 dB @ 100 MHz 2.83 dB @ 200 MHz 6.88 dB @ 1000 MHz 7.50 dB @ 1200 MHz 8.50 dB @ 1450 MHz 9.50 dB @ 2200 MHz 12.0 dB @ 3000 MHz

Cat5e ELECTRICAL CHARACTERISTICS

<u>Frequency</u>	<u>SRL</u>	<u>Return Loss</u>	<u>Attenuation</u>	<u>PS-NEXT</u>	<u>NEXT</u>	<u>ELFEXT</u>	<u>PS-ELFEXT</u>
<u>MHz</u>	<u>dB</u>	<u>dB</u>	<u>dB (100m)</u>	<u>dB</u>	<u>dB</u>	<u>dB</u>	<u>dB</u>
	<u>Minimum</u>	<u>Minimum</u>	<u>Maximum</u>	<u>Minimum</u>	<u>Minimum</u>	<u>Minimum</u>	<u>Minimum</u>
1	23.0	20.0	2.0	68.3	70.3	63.8	60.8
4	23.0	20.3	4.0	59.3	61.3	51.7	48.7
10	23.0	25.0	6.4	53.3	55.3	43.8	40.8
16	23.0	25.0	8.2	50.3	52.3	39.7	36.7
20	23.0	25.0	9.2	48.8	50.8	37.7	34.7
31.25	21.5	23.6	11.7	45.9	47.9	33.9	30.9
62.5	18.1	21.5	16.9	41.4	43.4	27.8	24.8
100	16.0	20.1	21.9	38.3	40.3	23.8	20.8
250	12.0	17.3	36.8	32.3	34.3	15.8	12.8
300	11.2	16.8	40.9	31.2	33.2	14.2	11.2
350	10.6	16.3	44.8	30.2	32.2	12.9	9.9

*Electricals are prior to cabling

Issue Date: August '10 Revision: 0

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744
FAX: 845-651-3564

Page 2 of 3

PO BOX 454
FLORIDA, NY 10921

techsupport@cctcable.com

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.