



PRODUCT SPECIFICATIONS

**CONVERGENT
CONNECTIVITY
TECHNOLOGY**

WB1034

Description:

16/2 Stranded bare copper conductors, shielded, wrapped with a water-blocking tape and overall jacketed

Applications:

Intercom Systems, Security Systems, Sound and Audio, Background Music, and Power-Limited Control Circuits. Outdoor Applications



CONSTRUCTION

Conductor:	16 AWG Bare Copper
Stranding:	7 Strand
Insulation Material:	Polyvinyl Chloride
Insulation Thickness:	0.008 in. (0.203 mm.) Nominal
Number of Conductors or Pairs:	2 Conductor
Shield:	Aluminum/Polyester Tape (100% Coverage)
Drain:	Stranded Tin Copper
Tape:	Water blocking tape
Jacket Material:	Polyethylene
Jacket Thickness:	0.020 in. (0.457 mm.) Nominal
Overall Cable Diameter:	0.230 in. (5.842 mm.) Nominal
Approx Cable Weight /1,000 ft.:	35 lbs.

ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage:	300 V, RMS
Insulation Colors:	Black, Red
DC Resistance per Conductor @ 20°C:	3.7358 Ω /1m'
Min. Bend Radius (Installation):	2.76 in.
Temperature Rating:	-20°C to +60°C

Issue Date: January '13 Revision: 0

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744
FAX: 845-651-3564

Page 1 of 1

techsupport@cctcable.com

PO BOX 454
FLORIDA, NY 10921

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.