



# PRODUCT SPECIFICATIONS

**CONVERGENT  
CONNECTIVITY  
TECHNOLOGY**

## WB106

### Description:

16/2 Stranded bare copper conductors, wrapped with a water-blocking tape and overall jacketed

### Applications:

Intercom Systems, Security Systems, Sound and Audio, Background Music, and Power-Limited Control Circuits. Outdoor Applications



## CONSTRUCTION

Conductor:	16 AWG Bare Copper
Stranding:	7 Strand
Insulation Material:	Polyvinyl Chloride
Insulation Thickness:	0.008 in. (0.203 mm.) Nominal
Number of Conductors or Pairs:	2 Conductor
Tape:	Water blocking tape
Jacket Material:	Polyethylene
Jacket Thickness:	0.018 in. (0.457 mm.) Nominal
Overall Cable Diameter:	0.205 in. (5.207 mm.) Nominal
Approx Cable Weight /1,000 ft.:	25 lbs.

## ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage:	300 V, RMS
Insulation Colors:	Black, Red
Temperature Rating:	-20°C to +60°C

Issue Date: August '12      Revision: 0

***THE STRONGEST LINK IN YOUR SUPPLY CHAIN***

PHONE: 866-905-6744  
FAX: 845-651-3564

Page 1 of 1

[techsupport@cctcable.com](mailto:techsupport@cctcable.com)

PO BOX 454  
FLORIDA, NY 10921

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.