




PRODUCT SPECIFICATIONS

**CONVERGENT
CONNECTIVITY
TECHNOLOGY**

WB5219

**Description:**

18AWG solid bare copper RG6/U 75 Ohm Non-Plenum coaxial cable with a water-blocking tape

Applications:

Video Display, Point-of-Sale Terminals. Local Area Network controls, Computers, Broadcast, and CATV. Suitable for outdoor use

CONSTRUCTION

Conductor:	18 AWG Bare Copper
Stranding:	Solid
Dielectric Material:	Cellular Polyethylene
Dielectric Core Diameter:	0.180 in. (4.572 mm.) Nominal
Braid Shield:	CCA
Tape:	Waterblocking Tape (100% coverage)
Jacket Material:	Polyethylene
Overall Cable Diameter:	0.275 in. (6.985 mm.) Nominal
Approx Cable Weight /1,000 ft.:	42 lbs.

ELECTRICAL & PHYSICAL PROPERTIES

Capacitance:	17.3pF/ft Nominal
Velocity of propagation:	78% Nominal
Characteristic Impedance:	75Ω Nominal
Nominal attenuation per 100ft:	0.70 dB @ 10 MHz 4.50 dB @ 400 MHz 1.50 dB @ 50 MHz 7.50 dB @ 900 MHz 2.10 dB @ 100 MHz 8.10 dB @ 1000 MHz
Temperature Rating:	-20°C to 60°C

Issue Date: July '11 Revision: 2

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744
FAX: 845-651-3564

Page 1 of 1

techsupport@cctcable.com

PO BOX 454
FLORIDA, NY 10921

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.