

PRODUCT SPECIFICATIONS

CONVERGENT CONNECTIVITY TECHNOLOGY

P5406

Description:	14AWG Solid Bare Copper RG-11/U 75 Ohm Plenum coaxial cable
Ratings/Approvals:	NEC Article 800, UL Subject 444, Type CMP, C(ETL)US, RoHS Compliant
Applications:	Computers, Broadcast, and CATV

CONSTRUCTION

Conductor:	14 AWG Copperweld
Stranding:	Solid
Dielectric Material:	Cellular FEP (Teflon)
Dielectric Core Diameter:	0.280 in. (7.112 mm.) Nominal
Foil Shield:	Aluminum/Polyester Tape (100% Coverage)
Braid Shield:	Aluminum
Foil Shield:	Aluminum/Polyester Tape (100% Coverage)
Braid Shield:	Aluminum
Jacket Material:	Plenum Polymer
Overall Cable Diameter:	0.405 in. (10.287mm.) Nominal
Approx Cable Weight /1,000 ft.:	75 lbs.

ELECTRICAL & PHYSICAL PROPERTIES

Capacitance:

Velocity of propagation:

Characteristic Impedance:

Nominal attenuation per 100ft:

Temperature Rating:

17.3pF/ft Nominal

78% Nominal

 75Ω Nominal

1.50 dB @ 100 MHz 2.20 dB @ 200 MHz 3.70 dB @ 500 MHz

-2°C to 60°C

Issue Date: August '15 Revision: 0

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744 FAX: 845-651-3564

techsupport@cctcable.com



PO BOX 454 FLORIDA, NY 10921 1



PRODUCT SPECIFICATIONS

CONVERGENT CONNECTIVITY TECHNOLOGY

P5406

Note: While Convergent Connectivity Technology has made every reasonable effort to ensure the accuracy of the information in this document, Convergent Connectivity Technology does not guarantee that it is error-free, nor does Convergent Connectivity Technology make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Convergent Connectivity Technology reserves the right to make any adjustments to the information contained herein at any time without notice. Convergent Connectivity Technology expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

Your signature constitutes that you have read and agreed to this specification sheet and upon confirmation of your order; this item may be non-cancelable and non-returnable.

Signature:

Company:

Date:



PO BOX 454 FLORIDA, NY 10921

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

Issue Date: August '15

PHONE: 866-905-6744 FAX: 845-651-3564

techsupport@cctcable.com

Revision: 0