



RS9003



Description: 14/4 High Strand Audio Cable, unshielded with an Overall PVC Jacket

Ratings/Approvals: NEC Article 800, UL Subject 444, Type CM/CL3R, FT4 C(ETL)US, RoHS Com-

Applications: Intercom Systems, Security Systems, Sound and Audio, Background Music, and Power-Limited Control Circuits. Indoor Applications. Suitable for Outdoor use. Oxygen free copper

CONSTRUCTION

Conductor: 14 AWG Bare Copper

Stranding: 105 x 34

Insulation Material: Polyvinyl Chloride

Insulation Thickness: 0.012 in. (0.304 mm.) Nominal

Number of Conductors or Pairs: 4 Conductor

Shield: N/A

Drain: N/A

Jacket Material: Polyvinyl Chloride

0.018 in. Nominal Jacket Thickness:

Overall Cable Diameter: 0.270 in. (Nominal

Approx Cable Weight /1,000 ft.: 73 lbs.

ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage: 300 V, RMS

Insulation Colors: Black, Red, White, Green

 -20° C to $+75^{\circ}$ C Temperature Rating:

Issue Date: November '10 Revision: 0

THE STRONGEST LINK IN YOUR SUPPLY CHAIN





PHONE: 866-905-6744 FAX: 845-651-3564

Page 1 of 1

PO BOX 454 FLORIDA, NY 10921

techsupport@cctcable.com



CONVERGENT CONNECTIVITY TECHNOLOGY

RS9004BK1S

Surface Print 3147706 c(ETL)us TYPE CMR 75C 12AWG ---RoHS COMPLIANT, + Sequential Footage Mark-

Jacket Color: Black

Note: While Convergent Connectivity Technology has made every reasonable effort to ensure the accuracy of the information in this document, Convergent Connectivity Technology does not guarantee that it is error-free, nor does Convergent Connectivity Technology make any other representation, warranty, or guarantee that the information is accurate, correct, reliable or current. Convergent Connectivity Technology reserves the right to make any adjustments to the information contained herein at any time without notice. Convergent Connectivity Technology expressly disclaims all implied warranties regarding the information contained herein, including but not limited to, any implied warranties of merchantability or fitness for particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice.

specification sheet	t and upon confirmation of your order; this item lable and non-returnable.
Signature:	
Company:	
Date:	

THE STRONGEST LINK IN YOUR SUPPLY CHAIN

PHONE: 866-905-6744 FAX: 845-651-3564

Page 1 of 1

PO BOX 454 FLORIDA, NY 10921

techsupport@cctcable.com

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.