



PRODUCT SPECIFICATIONS

CONVERGENT
CONNECTIVITY
TECHNOLOGY

RS9006



- Description:** 16/2 High Strand Audio Cable, unshielded with an Overall PVC Jacket
- Ratings/Approvals:** NEC Article 800, UL Subject 444, Type CMR/CL3R FT4, C(ETL)US, RoHS Com-
- Applications:** Intercom Systems, Security Systems, Sound and Audio, Background Music, and Power-Limited Control Circuits. Indoor Applications . Suitable for outdoor use. Oxygen free Copper-

CONSTRUCTION

Conductor:	16 AWG Bare Copper
Stranding:	65 x 34
Insulation Material:	Polyvinyl Chloride
Insulation Thickness:	0.012 in. (0.304 mm.) Nominal
Number of Conductors or Pairs:	2 Conductor
Shield:	N/A
Drain:	N/A
Jacket Material:	Polyvinyl Chloride
Jacket Thickness:	0.018 in. (0.457 mm.) Nominal
Overall Cable Diameter:	0.204 in. (5.181 mm.) Nominal
Approx Cable Weight /1,000 ft.:	38 lbs.

ELECTRICAL & PHYSICAL PROPERTIES

Operative Voltage:	300 V, RMS
Insulation Colors:	Black, Red
Temperature Rating:	-20°C to +75°C

Issue Date: November '10 Revision: 0

THE STRONGEST LINK IN YOUR SUPPLY CHAIN



PHONE: 866-905-6744
FAX: 845-651-3564

Page 1 of 1

techsupport@cctcable.com

PO BOX 454
FLORIDA, NY 10921

The information provided herein is, to the best of our knowledge, true and accurate. Since conditions of use are beyond our control, all information presented is without guarantee or responsibility on our part. We disclaim all liability in connection with the use of information contained herein or otherwise.